

## DATASHEET

# Johnstone's

## Johnstone's Professional Interior Timber Floor (Satin)



Product Code:  
483120



### Johnstone's Professional Interior Timber Floor (Satin)

An exceptionally durable, fast drying, water based, clear Satin finish for interior timber and timber flooring. Johnstone's Professional Interior Timber Floor (Satin) has high resistance to abrasion. Very qualitative decoration/uniformed coverage to timber once dry. Highlights the natural beauty of timber features and keeps the initial original colour of the coated timber.

### USES

All high domestic interior hard and softwood timber substrates including timber flooring.

### FEATURES AND BENEFITS

<b>EASE OF APPLICATION (JOHNSTONE'S ONLY)</b>	The application properties of Johnstone's make it easy to apply to all timber substrates
<b>GREATER TRANSPARENCY</b>	Designed for greater transparency to allow the timber grain to be more visible
<b>FAST DRYING</b>	Assist project completion timelines with fast drying properties
<b>WATER BASED FORMULA</b>	Easy clean up with water

### PRODUCT SPECIFICATIONS

<b>1L AVAILABLE SIZES</b>	1L
<b>4L AVAILABLE SIZES</b>	4L
<b>10L AVAILABLE SIZES</b>	10L
<b>CLEAN UP</b>	Water clean up
<b>DRY TIMES: RECOAT</b>	3 hours at 23 deg C – 50% HR
<b>DRY TIMES: TOUCH DRY</b>	30 minutes at 23 deg C – 50% HR

## DATASHEET

<b>VOC LEVELS</b>	110 g/L
<b>GLOSS LEVEL</b>	Matt: max. 10; Satin 20 – 30. (% at a 60 degree angle)

## SURFACE PREPARATION

<b>JOHNSTONE'S INTERIOR TIMBER</b>	Timber should be prepared and polished by sanding. Be sure there is no former coatings of any product (varnish, wax, oil etc.) left before applying. Substrate needs to be studied to establish exact preparation requirements. Check with timber supplier or installer
<b>SOFTWOOD TIMBER</b>	Ensure timber surface is dry, clean and free from dirt and debris prior to application

## APPLICATION

<b>APPLICATOR PAD</b>	Ensure applicator pad has a generous amount of product on the pad. Apply pad to timber surface ensuring liberal and even application of product to timber surface. Ensure entire length of the decking board is coated prior to drying.
<b>COVERAGE</b>	Up to 10m <sup>2</sup> /L dependent on timber porosity
<b>COATS REQUIRED</b>	3
<b>BRUSH-JOHNSTONE'S INTERIOR</b>	<ol style="list-style-type: none"> <li>1. Use a flat blade paint stirrer to stir product thoroughly before and during use. Please note: This product does not require thinning.</li> <li>2. For application around floor edges use a narrow brush or applicator to cut in. Apply to the edges of the area first, then apply along the length of the timber boards. During application keep applied area wet and use gentle strokes along the grain to redistribute the product evenly. Avoid over working the coating as this can result in a patchy finish. Leave to dry for 3 hours then sand gently to achieve a smooth finish. Remove any dust or other contaminants. Apply (at least) two additional coats using the same process.</li> </ol>

## PRECAUTIONS

<b>FIRST AID INFORMATION</b>	<p>IF SWALLOWED</p> <p>Do NOT induce vomiting. Seek medical advice immediately.</p> <p>EYE CONTACT</p> <p>Flush with plenty of water. Always seek medical advice.</p> <p>SKIN CONTACT</p> <p>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.</p> <p>INHALATION</p> <p>Remove to fresh air, seek medical advice if breathing is laboured.</p> <p>AUSTRALIA</p> <p>24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: <a href="http://www.taubmans.com.au">www.taubmans.com.au</a></p>
<b>ENVIRONMENT INFORMATION</b>	Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit <a href="http://paintback.com.au">paintback.com.au</a>
<b>GENERAL SAFETY INFORMATION</b>	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area. Do not store below 5 deg C temperature. Keep containers sealed when not in use

## DATASHEET

**DISCLAIMER**

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

**CUSTOMER SERVICE/COMPANY CONTACT**

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)