

DATASHEET

Johnstone's Professional Slip Resistant Deck Oil



Product Code:
481210



Johnstone's Professional Slip Resistant Deck Oil

Exceptionally durable, fast drying, water based & slip resistant. Best for protecting hardwood and treated pine decking around pools and wet areas.



USES

Hardwood and treated pine decking around pools & wet areas

FEATURES AND BENEFITS

AUSTRALIAN MADE	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
SLIP RESISTANCE	Johnstone's Professional Slip Resistant Deck Oil is tested to AS4586-2013 Slip resistant classification of new pedestrian surface materials OIL-WET Ramp = Slip Resistance Assessment Group R11
UV PROTECTION	Blocks out harmful UV rays for longer lasting results
MOULD PROTECTION (JOHNSTONE'S ONLY)	Encapsulated biocide which is released slowly. Slow release means the coating resists mould growth for up to 2 times longer versus conventional woodcare products
EASE OF APPLICATION (JOHNSTONE'S ONLY)	The application properties of Johnstone's make it easy to apply to all timber substrates
GREATER TRANSPARENCY	Designed for greater transparency to allow the timber grain to be more visible
WATER BASED FORMULA	Easy clean up with water
IDEAL SURFACE JOHNSTONES ONLY	Exterior Soft and Hardwood Timber

PRODUCT SPECIFICATIONS

DATASHEET

APPEARANCE	Semi-transparent, low lustre, slightly textured
CLEAN UP	Water
VOC LEVELS	37 g/Litre
DRY TIMES: TOUCH DRY	30 minutes (Note: All timings quoted at 25oC and 50% humidity. Cooler or humid conditions may require longer.)
DRY TIMES: RECOAT	1 hour (Note: All timings quoted at 25oC and 50% humidity. Cooler or humid conditions may require longer.)
1L AVAILABLE SIZES	1l
4L AVAILABLE SIZES	4l
10L AVAILABLE SIZES	10l

SURFACE PREPARATION

TEMPERATURE MIN	10 (°C)
TEMPERATURE MAX	35 (°C)
RECOATTEMPDEGREES	25 (°C)
RECOATHUMIDITYPERCENTAGE	50 (%)
NEW HARDWOOD TIMBER (JOHNSTONE'S)	Allow the timber to naturally weather for 6 weeks. During this period, wet timber with a garden hose as regularly as possible. This will flush the natural timber tannins from the timber substrate and reduce the risk of timber tannin residue appearing once exterior oil has been applied. Alternatively, apply Johnstone's Professional Tannin & Oil Remover followed by Johnstone's Professional Deck & Timber Cleaner following label instructions. Allow to completely dry. Lightly sand timber surface. This will raise the fibres of the timber grain and provide a greater key for the Johnstone's Professional Timber Oil to adhere to
PREVIOUSLY PAINTED OR VANISHED TIMBER	Remove previously coated material back to bare timber using Johnstone's Professional Timber Stripper, or by sanding. Clean timber with Johnstone's Professional Deck & Timber Cleaner following label instructions to remove any contaminants such as mould or tannin bleed residue. Allow to completely dry prior to coating
PREVIOUSLY STAINED AND OILED TIMBER	Clean timber with Johnstone's Professional Deck & Timber Cleaner, rinse off timber substrate following label instructions and allow to completely dry. Lightly sand the timber surface to improve adhesion. Ensure timber is free from dirt, dust and contaminants prior to the application
WEATHERED AND GREY TIMBER DECKING	For best results, clean timber with Johnstone's Professional Deck & Timber Cleaner following label instructions. Use a high pressure washer to remove residue and allow to completely dry. Additional light sand may be required to remove any grey areas not removed by Johnstone's Professional Deck & Timber Cleaner. Ensure surface is dirt and dust free prior to the application

APPLICATION

WET FILM THICKNESS	100 - 125 microns
DRY FILM THICKNESS	17 - 20 microns

DATASHEET

STIRRING	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
NAP ROLLER	Brush, Deck Brush, Lambs Wool Applicator Pad
COVERAGE	Up to 12m ² per litre (Subject to timber porosity, species and condition)
APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS	10
APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS	35
COATS REQUIRED	Three
EXTERIOR OIL ALL APPLICATORS	Brush, Deck Brush, Lambs Wool Applicator Pad

PRECAUTIONS

GENERAL SAFETY INFORMATION	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area. Do not store below 5 deg C temperature. Keep containers sealed when not in use
FIRST AID INFORMATION	<p>IF SWALLOWED</p> <p>Do NOT induce vomiting. Seek medical advice immediately.</p> <p>EYE CONTACT</p> <p>Flush with plenty of water. Always seek medical advice.</p> <p>SKIN CONTACT</p> <p>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.</p> <p>INHALATION</p> <p>Remove to fresh air, seek medical advice if breathing is laboured.</p> <p>AUSTRALIA</p> <p>24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au</p>
ENVIRONMENT INFORMATION	Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

ENVIRONMENT & SAFETY

WARRANTY INFORMATION	<p>Johnstone's Professional decking and exterior range (excluding Interior / Exterior Clear) is guaranteed against peeling, flaking and blistering for 12 months if used in accordance with printed directions on pack and applied to suitable and properly prepared surfaces. If this guarantee is not met, we will replace the product or refund your money. This guarantee is given by PPG Industries Australia Pty Limited and applies to defects in the manufacture or formulation of the product. This guarantee does not cover peeling, flaking and blistering caused by failure of previously applied products, contaminated substrates, unsound problems caused by environmental or underlying structural issues, or product failure caused by other factors beyond our control.</p> <p>We are not liable for the cost of labour or any other direct or indirect loss or damage arising from a breach of this guarantee. Customers are responsible for all costs of claiming under this guarantee. To claim, customers must write to us or call our Customer Service number to request a claim form. The benefits provided by this guarantee are in addition to other rights and remedies under the law. If you are a consumer within the meaning of the Australian or New Zealand Consumer Law: Our goods come with guarantees that cannot be excluded under the Australian Consumer Law and Consumer Guarantees Act, respectively. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.</p>
-----------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au