

## DATASHEET

# Johnstone's Professional Deck and Timber Cleaner



Product Code:  
481349



## Johnstone's Professional Deck and Timber Cleaner

A powerful, high strength timber cleaner that contains a naturally occurring, bio-degradable, organic acid. Used to clean all timber prior to coating, it will help restore and prepare weathered, grey, rust or tannin-stained, or mould and mildew affected timber. Gel formula – ideal for vertical surfaces

## USES

Brightening and rejuvenating grey, weathered, and stained timber. Also removes mould and mildew

## FEATURES AND BENEFITS

<b>EASE OF APPLICATION (JOHNSTONE'S ONLY)</b>	The application properties of Johnstone's make it easy to apply to all timber substrates
<b>WATER BASED FORMULA</b>	Easy clean up with water
<b>IDEAL SURFACE JOHNSTONES ONLY</b>	Exterior Soft and Hardwood Timber

## PRODUCT SPECIFICATIONS

<b>VOC LEVELS</b>	<10 g/Litre
<b>DRY TIMES: TOUCH DRY</b>	Do not let product dry on timber surface
<b>DRY TIMES: RECOAT</b>	Do not let product dry on timber surface
<b>1L AVAILABLE SIZES</b>	1L
<b>4L AVAILABLE SIZES</b>	4L

## SURFACE PREPARATION

## DATASHEET

TEMPERATURE MIN	10 (°C)
TEMPERATURE MAX	35 (°C)
RECOATTEMPDEGREES	25 (°C)
RECOATHUMIDITYPERCENTAGE	50 (%)
NEW HARDWOOD TIMBER (JOHNSTONE'S)	Allow the timber to naturally weather for 6 weeks. During this period, wet timber with a garden hose as regularly as possible. This will flush the natural timber tannins from the timber substrate and reduce the risk of timber tannin residue appearing once exterior oil has been applied. Alternatively, apply Johnstone's Professional Tannin & Oil Remover followed by Johnstone's Professional Deck & Timber Cleaner following label instructions. Allow to completely dry. Lightly sand timber surface. This will raise the fibres of the timber grain and provide a greater key for the Johnstone's Professional Timber Oil to adhere to
SOFTWOOD TIMBER	Ensure timber surface is dry, clean and free from dirt and debris prior to application
PREVIOUSLY PAINTED OR VANISHED TIMBER	Remove previously coated material back to bare timber using Johnstone's Professional Timber Stripper, or by sanding. Clean timber with Johnstone's Professional Deck & Timber Cleaner following label instructions to remove any contaminants such as mould or tannin bleed residue. Allow to completely dry prior to coating
PREVIOUSLY STAINED AND OILED TIMBER	Clean timber with Johnstone's Professional Deck & Timber Cleaner, rinse off timber substrate following label instructions and allow to completely dry. Lightly sand the timber surface to improve adhesion. Ensure timber is free from dirt, dust and contaminants prior to the application
WEATHERED AND GREY TIMBER DECKING	For best results, clean timber with Johnstone's Professional Deck & Timber Cleaner following label instructions. Use a high pressure washer to remove residue and allow to completely dry. Additional light sand may be required to remove any grey areas not removed by Johnstone's Professional Deck & Timber Cleaner. Ensure surface is dirt and dust free prior to the application
DECK CLEANER OR TANNIN REMOVER	Yes

## APPLICATION

MIXING RATES	Dilute 4:1 with water in a bucket or roller tray and apply to the timber surface with a stiff bristle brush, broom or scouring pad. Scrub Johnstone's Deck & Timber Cleaner gel into the timber with a stiff bristle brush. Leave on the surface of the timber for 10-15 minutes. If necessary apply more product or a light spray of water to keep the surface damp throughout this period. Do not allow Johnstone's Deck & Timber Cleaner to dry on the timber surface. Rinse off exterior timber surfaces thoroughly using maximum pressure from a garden hose or using a high pressure water cleaner. Allow to thoroughly dry prior to applying any further Johnstone's products
APPLICATION TEMPERATURE MINIMUM DEGREES CELSIUS	10
APPLICATION TEMPERATURE MAXIMUM DEGREES CELSIUS	35
STIFF BRISTLE BRUSH	Stiff bristle brush

## PRECAUTIONS

GENERAL SAFETY INFORMATION	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area. Do not store below 5 deg C temperature. Keep containers sealed when not in use
FIRST AID INFORMATION	IF SWALLOWED Do NOT induce vomiting. Seek medical advice immediately. EYE CONTACT

## DATASHEET

Flush with plenty of water. Always seek medical advice.

### SKIN CONTACT

Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.

### INHALATION

Remove to fresh air, seek medical advice if breathing is laboured.

### AUSTRALIA

24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)

### ENVIRONMENT INFORMATION

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit [paintback.com.au](http://paintback.com.au)

## DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

## CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)