

DATASHEET

# Johnstone's Professional Exterior Timber Oil



Product Code:  
481100



## Johnstone's Professional Exterior Timber Oil

Extremely durable, fast drying superior water based oil. Best for protecting vertical hardwood and softwood exterior timber cladding, windows, doors, bi-folds, gates and pergolas.



## USES

Vertical hardwood and softwood exterior timber cladding, windows, doors, bi-folds, gates & pergolas. New and weathered exterior hard and soft timber species, such as Western Red Cedar window and door joinery. Not suitable for decks.

## FEATURES AND BENEFITS

<b>FAST DRYING</b>	Assist project completion timelines with fast drying properties
<b>AUSTRALIAN MADE</b>	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
<b>UV PROTECTION</b>	Blocks out harmful UV rays for longer lasting results
<b>EASE OF APPLICATION (JOHNSTONE'S ONLY)</b>	The application properties of Johnstone's make it easy to apply to all timber substrates
<b>WATER BASED FORMULA</b>	Easy clean up with water
<b>IDEAL SURFACE JOHNSTONES ONLY</b>	Exterior Soft and Hardwood Timber

## PRODUCT SPECIFICATIONS

<b>CLEAN UP</b>	Water
<b>APPEARANCE</b>	Semi-transparent, low lustre
<b>VOC LEVELS</b>	48g/Litre

## DATASHEET

<b>DRY TIMES: TOUCH DRY</b>	30 mins
<b>DRY TIMES: RECOAT</b>	1 hour
<b>1L AVAILABLE SIZES</b>	1L
<b>4L AVAILABLE SIZES</b>	4L
<b>10L AVAILABLE SIZES</b>	10L

## SURFACE PREPARATION

<b>TEMPERATURE MIN</b>	10 (°C)
<b>TEMPERATURE MAX</b>	35 (°C)
<b>RECOATTEMPDEGREES</b>	25 (°C)
<b>RECOATHUMIDITYPERCENTAGE</b>	50 (%)
<b>NEW HARDWOOD TIMBER (JOHNSTONE'S)</b>	Allow the timber to naturally weather for 6 weeks. During this period, wet timber with a garden hose as regularly as possible. This will flush the natural timber tannins from the timber substrate and reduce the risk of timber tannin residue appearing once exterior oil has been applied. Alternatively, apply Johnstone's Professional Tannin & Oil Remover followed by Johnstone's Professional Deck & Timber Cleaner following label instructions. Allow to completely dry. Lightly sand timber surface. This will raise the fibres of the timber grain and provide a greater key for the Johnstone's Professional Timber Oil to adhere to
<b>SOFTWOOD TIMBER</b>	Ensure timber surface is dry, clean and free from dirt and debris prior to application
<b>PREVIOUSLY PAINTED OR VANISHED TIMBER</b>	Remove previously coated material back to bare timber using Johnstone's Professional Timber Stripper, or by sanding. Clean timber with Johnstone's Professional Deck & Timber Cleaner following label instructions to remove any contaminants such as mould or tannin bleed residue. Allow to completely dry prior to coating
<b>PREVIOUSLY STAINED AND OILED TIMBER</b>	Clean timber with Johnstone's Professional Deck & Timber Cleaner, rinse off timber substrate following label instructions and allow to completely dry. Lightly sand the timber surface to improve adhesion. Ensure timber is free from dirt, dust and contaminants prior to the application
<b>WEATHERED AND GREY TIMBER DECKING</b>	For best results, clean timber with Johnstone's Professional Deck & Timber Cleaner following label instructions. Use a high pressure washer to remove residue and allow to completely dry. Additional light sand may be required to remove any grey areas not removed by Johnstone's Professional Deck & Timber Cleaner. Ensure surface is dirt and dust free prior to the application

## APPLICATION

<b>DRY FILM THICKNESS</b>	18 Microns at 12m <sup>2</sup> spread rate
<b>NAP ROLLER</b>	Brush, Deck Brush, Lambs Wool Applicator Pad
<b>COVERAGE</b>	Up to 12m <sup>2</sup> per litre (Subject to timber porosity, species and condition)
<b>APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS</b>	10

## DATASHEET

<b>APPLICATION TEMPERATURE</b>	35
<b>MAXIMUM DEGREES CELCIUS</b>	
<b>COATS REQUIRED</b>	Three
<b>EXTERIOR OIL ALL APPLICATORS</b>	Brush and Microfibre Roller

## PRECAUTIONS

<b>GENERAL SAFETY INFORMATION</b>	<p><b>WALL PAINTS</b></p> <p><b>SAFETY</b></p> <p>Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p> <p><b>CEILING</b></p> <p><b>SAFETY</b></p> <p>Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p>
<b>FIRST AID INFORMATION</b>	<p>IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.</p> <p>EYE CONTACT - Flush with plenty of water. Always seek medical advice.</p> <p>SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.</p> <p>INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.</p> <p>AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: <a href="http://www.taubmans.com.au">www.taubmans.com.au</a></p>
<b>ENVIRONMENT INFORMATION</b>	<p>Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit <a href="http://paintback.com.au">paintback.com.au</a></p>

## DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

## CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)