

DATASHEET

Johnstone's Professional Interior Exterior Clear Gloss



Product Code:
481121



Johnstone's Professional Interior Exterior Clear Gloss

Durable, fast drying, non-yellowing clear finish available in 15 trend colours. Best to enhance the natural beauty of interior and exterior timber windows, doors and trims where a colourless clear coating is required.

USES

Enhances the natural beauty of interior and exterior timber windows, doors and trims where a colourless clear coating is required.

FEATURES AND BENEFITS

MOULD RESISTANT	Prevents the growth of mould, mildew and fungus in damp areas
INTERNAL AND EXTERNAL	Suitable for use in internal and external areas
FAST DRYING	Assist project completion timelines with fast drying properties
AUSTRALIAN MADE	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
UV PROTECTION	Blocks out harmful UV rays for longer lasting results
MOULD PROTECTION (JOHNSTONE'S ONLY)	Encapsulated biocide which is released slowly. Slow release means the coating resists mould growth for up to 2 times longer versus conventional woodcare products
EASE OF APPLICATION (JOHNSTONE'S ONLY)	The application properties of Johnstone's make it easy to apply to all timber substrates
GREATER TRANSPARENCY	Designed for greater transparency to allow the timber grain to be more visible
WATER BASED FORMULA	Easy clean up with water
IDEAL SURFACE JOHNSTONES ONLY	Exterior Soft and Hardwood Timber

PRODUCT SPECIFICATIONS

DATASHEET

CLEAN UP	Water
DRY FILM THICKNESS	25 Microns at 12m2 spread rate
GLOSS	Highest gloss level that is hard wearing with an easy to clean surface. Ideal for areas subject to heavy wear such as doors and trims, exterior walls (recommended for weatherboards, roof and trims), cement render / masonry, timber, galvanised iron, PVC piping and steel. Not suitable for surfaces used to collect drinking water
VOC LEVELS	85g/Litre
DRY TIMES: TOUCH DRY	30 minutes (Note: All timings quoted at 25oC and 50% humidity. Cooler or humid conditions may require longer.)
DRY TIMES: RECOAT	1 hour (Note: All timings quoted at 25oC and 50% humidity. Cooler or humid conditions may require longer.)
1L AVAILABLE SIZES	1L
4L AVAILABLE SIZES	4L
10L AVAILABLE SIZES	10L

APPLICATION

NAP ROLLER	Brush, Deck Brush, Lambs Wool Applicator Pad
COVERAGE	Up to 12m2 per litre (Subject to timber porosity, species and condition)
APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS	10
APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS	35
COATS REQUIRED	Three
EXTERIOR OIL ALL APPLICATORS	Brush

PRECAUTIONS

GENERAL SAFETY INFORMATION	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area. Do not store below 5 deg C temperature. Keep containers sealed when not in use
FIRST AID INFORMATION	<p>IF SWALLOWED</p> <p>Do NOT induce vomiting. Seek medical advice immediately.</p> <p>EYE CONTACT</p> <p>Flush with plenty of water. Always seek medical advice.</p> <p>SKIN CONTACT</p> <p>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.</p> <p>INHALATION</p> <p>Remove to fresh air, seek medical advice if breathing is laboured.</p> <p>AUSTRALIA</p> <p>24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further</p>

DATASHEET

information: www.taubmans.com.au**ENVIRONMENT
INFORMATION**

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACTTaubmans Customer Service: 131 686 Further information: www.taubmans.com.au