

DATASHEET

Johnstone's Professional Timber Stripper



Product Code:
481359



Johnstone's Professional Timber Stripper

Removes most water and oil based timber coatings, including acrylics, polyurethanes and varnishes.

USES

Interior and exterior. It quickly and effectively removes most water and oil-based timber coatings including acrylics, polyurethanes and varnishes, removing multiple layers in a single application. Most exterior and interior timber surfaces. Note: Not suitable for epoxies and 2-Pack oil based coatings. Do not use on plastic surfaces, vinyl, masonite or rubber

FEATURES AND BENEFITS

EASE OF APPLICATION (JOHNSTONE'S ONLY)

The application properties of Johnstone's make it easy to apply to all timber substrates

WATER BASED FORMULA

Easy clean up with water

PRODUCT SPECIFICATIONS

VOC LEVELS

600g/Litre

DRY TIMES: TOUCH DRY

Do not let product dry on timber surface

DRY TIMES: RECOAT

Do not let product dry on timber surface

1L AVAILABLE SIZES

1L

4L AVAILABLE SIZES

4L

SURFACE PREPARATION

TEMPERATURE MIN

10 (°C)

TEMPERATURE MAX

35 (°C)

DATASHEET

RECOATTEMPDEGREES	25 (°C)
RECOATHUMIDITYPERCENTAGE	50 (%)
NEW HARDWOOD TIMBER (JOHNSTONE'S)	Allow the timber to naturally weather for 6 weeks. During this period, wet timber with a garden hose as regularly as possible. This will flush the natural timber tannins from the timber substrate and reduce the risk of timber tannin residue appearing once exterior oil has been applied. Alternatively, apply Johnstone's Professional Tannin & Oil Remover followed by Johnstone's Professional Deck & Timber Cleaner following label instructions. Allow to completely dry. Lightly sand timber surface. This will raise the fibres of the timber grain and provide a greater key for the Johnstone's Professional Timber Oil to adhere to
SOFTWOOD TIMBER	Ensure timber surface is dry, clean and free from dirt and debris prior to application
PREVIOUSLY PAINTED OR VANISHED TIMBER	Remove previously coated material back to bare timber using Johnstone's Professional Timber Stripper, or by sanding. Clean timber with Johnstone's Professional Deck & Timber Cleaner following label instructions to remove any contaminants such as mould or tannin bleed residue. Allow to completely dry prior to coating
PREVIOUSLY STAINED AND OILED TIMBER	Clean timber with Johnstone's Professional Deck & Timber Cleaner, rinse off timber substrate following label instructions and allow to completely dry. Lightly sand the timber surface to improve adhesion. Ensure timber is free from dirt, dust and contaminants prior to the application

APPLICATION

WET FILM THICKNESS	Do not let product dry on timber surface
DRY FILM THICKNESS	Do not let product dry on timber surface
BRUSH	Stir paint in a circular lifting motion for 5 minutes before use. Apply two coats by brush, with 2 hours between each coat. Paint the corners and edges with a narrow brush. Avoid using poor quality or worn brushes as they can adversely affect the final finish.
APPLICATION TEMPERATURE MINIMUM DEGREES CELSIUS	10
APPLICATION TEMPERATURE MAXIMUM DEGREES CELSIUS	35
EXTERIOR OIL ALL APPLICATORS	Brush
COVERAGE	Approximately 0.5 square meters per litre when applied 2mm thick on a horizontal surface.

PRECAUTIONS

GENERAL SAFETY INFORMATION	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area. Do not store below 5 deg C temperature. Keep containers sealed when not in use
FIRST AID INFORMATION	<p>IF SWALLOWED</p> <p>Do NOT induce vomiting. Seek medical advice immediately.</p> <p>EYE CONTACT</p> <p>Flush with plenty of water. Always seek medical advice.</p> <p>SKIN CONTACT</p> <p>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.</p> <p>INHALATION</p> <p>Remove to fresh air, seek medical advice if breathing is laboured.</p> <p>AUSTRALIA</p> <p>24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further</p>

DATASHEET

information: www.taubmans.com.au

ENVIRONMENT INFORMATION

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au