

DATASHEET

# Johnstone's Professional Exterior Deck Oil



Product Code:  
481200



## Johnstone's Professional Exterior Deck Oil

Exceptionally durable, fast drying, long lasting, water based oil. Best for protecting hardwood and softwood exterior timber decks.



## USES

Hardwood and softwood exterior timber decks

## FEATURES AND BENEFITS

<b>FAST DRYING</b>	Assist project completion timelines with fast drying properties
<b>AUSTRALIAN MADE</b>	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
<b>UV PROTECTION</b>	Blocks out harmful UV rays for longer lasting results
<b>MOULD PROTECTION (JOHNSTONE'S ONLY)</b>	Encapsulated biocide which is released slowly. Slow release means the coating resists mould growth for up to 2 times longer versus conventional woodcare products
<b>EASE OF APPLICATION (JOHNSTONE'S ONLY)</b>	The application properties of Johnstone's make it easy to apply to all timber substrates
<b>GREATER TRANSPARENCY</b>	Designed for greater transparency to allow the timber grain to be more visible
<b>WATER BASED FORMULA</b>	Easy clean up with water
<b>IDEAL SURFACE JOHNSTONES ONLY</b>	Exterior Soft and Hardwood Timber

## PRODUCT SPECIFICATIONS

<b>DRY FILM THICKNESS</b>	17 Microns at 12m <sup>2</sup> spread rate
---------------------------	--

## DATASHEET

<b>VOC LEVELS</b>	37 g/Litre
<b>DRY TIMES: TOUCH DRY</b>	30 mins (Note: All timings quoted at 25 C and 50% humidity. Cooler or humid conditions may require longer.)
<b>DRY TIMES: RECOAT</b>	1 hour (Note: All timings quoted at 25 C and 50% humidity. Cooler or humid conditions may require longer.)
<b>1L AVAILABLE SIZES</b>	1l
<b>4L AVAILABLE SIZES</b>	4l
<b>10L AVAILABLE SIZES</b>	10l

## SURFACE PREPARATION

<b>TEMPERATURE MIN</b>	10 (°C)
<b>TEMPERATURE MAX</b>	35 (°C)
<b>RECOATTEMPDEGREES</b>	25 (°C)
<b>RECOATHUMIDITYPERCENTAGE</b>	50 (%)
<b>NEW HARDWOOD TIMBER (JOHNSTONE'S)</b>	Allow the timber to naturally weather for 6 weeks. During this period, wet timber with a garden hose as regularly as possible. This will flush the natural timber tannins from the timber substrate and reduce the risk of timber tannin residue appearing once exterior oil has been applied. Alternatively, apply Johnstone's Professional Tannin & Oil Remover followed by Johnstone's Professional Deck & Timber Cleaner following label instructions. Allow to completely dry. Lightly sand timber surface. This will raise the fibres of the timber grain and provide a greater key for the Johnstone's Professional Timber Oil to adhere to
<b>SOFTWOOD TIMBER</b>	Ensure timber surface is dry, clean and free from dirt and debris prior to application
<b>PREVIOUSLY PAINTED OR VANISHED TIMBER</b>	Remove previously coated material back to bare timber using Johnstone's Professional Timber Stripper, or by sanding. Clean timber with Johnstone's Professional Deck & Timber Cleaner following label instructions to remove any contaminants such as mould or tannin bleed residue. Allow to completely dry prior to coating
<b>PREVIOUSLY STAINED AND OILED TIMBER</b>	Clean timber with Johnstone's Professional Deck & Timber Cleaner, rinse off timber substrate following label instructions and allow to completely dry. Lightly sand the timber surface to improve adhesion. Ensure timber is free from dirt, dust and contaminants prior to the application
<b>WEATHERED AND GREY TIMBER DECKING</b>	For best results, clean timber with Johnstone's Professional Deck & Timber Cleaner following label instructions. Use a high pressure washer to remove residue and allow to completely dry. Additional light sand may be required to remove any grey areas not removed by Johnstone's Professional Deck & Timber Cleaner. Ensure surface is dirt and dust free prior to the application

## APPLICATION

<b>NAP ROLLER</b>	Brush, Deck Brush, Lambs Wool Applicator Pad
<b>DECKING BRUSH</b>	Using a good quality brush, apply liberally and evenly to timber surface ensuring any end grain is coated. Ensure entire decking board is coated prior to drying.
<b>COVERAGE</b>	Up to 12m <sup>2</sup> per litre (Subject to timber porosity, species and condition)

## DATASHEET

<b>MAINTENANCE - DECKING</b>	Re-apply as the timber changes colour and presents a dull appearance or when water repellency diminishes due to weathering. Follow surface preparation instructions
<b>APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS</b>	10
<b>APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS</b>	35
<b>COATS REQUIRED</b>	Three
<b>EXTERIOR OIL ALL APPLICATORS</b>	Brush, Deck Brush, Lambs Wool Applicator Pad

## PRECAUTIONS

<b>GENERAL SAFETY INFORMATION</b>	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area. Do not store below 5 deg C temperature. Keep containers sealed when not in use
<b>FIRST AID INFORMATION</b>	<p>IF SWALLOWED</p> <p>Do NOT induce vomiting. Seek medical advice immediately.</p> <p>EYE CONTACT</p> <p>Flush with plenty of water. Always seek medical advice.</p> <p>SKIN CONTACT</p> <p>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.</p> <p>INHALATION</p> <p>Remove to fresh air, seek medical advice if breathing is laboured.</p> <p>AUSTRALIA</p> <p>24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: <a href="http://www.taubmans.com.au">www.taubmans.com.au</a></p>
<b>ENVIRONMENT INFORMATION</b>	Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit <a href="http://paintback.com.au">paintback.com.au</a>

## ENVIRONMENT & SAFETY

<b>WARRANTY INFORMATION</b>	<p>Johnstone's Professional decking and exterior range (excluding Interior / Exterior Clear) is guaranteed against peeling, flaking and blistering for 12 months if used in accordance with printed directions on pack and applied to suitable and properly prepared surfaces. If this guarantee is not met, we will replace the product or refund your money. This guarantee is given by PPG Industries Australia Pty Limited and applies to defects in the manufacture or formulation of the product. This guarantee does not cover peeling, flaking and blistering caused by failure of previously applied products, contaminated substrates, unsound problems caused by environmental or underlying structural issues, or product failure caused by other factors beyond our control.</p> <p>We are not liable for the cost of labour or any other direct or indirect loss or damage arising from a breach of this guarantee. Customers are responsible for all costs of claiming under this guarantee. To claim, customers must write to us or call our Customer Service number to request a claim form. The benefits provided by this guarantee are in addition to other rights and remedies under the law. If you are a consumer within the meaning of the Australian or New Zealand Consumer Law: Our goods come with guarantees that cannot be excluded under the Australian Consumer Law and Consumer Guarantees Act, respectively. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.</p>
-----------------------------	---

## DISCLAIMER

## DATASHEET

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

## CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)